




## BEARING-MALAYSIA SDN.BHD.



71924 ACB/HCP4A Bearing 2D drawings and 3D CAD models

120 mm x 165 mm x 22 mm SKF 71924  
ACB/HCP4A angular contact ball bearings

Bearing No. 71924 ACB/HCP4A

Size	165x120x22 mm
Bore Diameter	165 mm
Outer Diameter	120 mm
Width	22 mm
d	120 mm
D	165 mm
B	22 mm
d <sub>1</sub>	136.92 mm
d <sub>2</sub>	135 mm
D <sub>2</sub>	151.9 mm
r <sub>1,2</sub> - min.	1.1 mm
r <sub>3,4</sub> - min.	0.6 mm
a	49.2 mm
d <sub>a</sub> - min.	126 mm
d <sub>b</sub> - min.	126 mm
D <sub>a</sub> - max.	159 mm
D <sub>b</sub> - max.	161.8 mm
r <sub>a</sub> - max.	1 mm
r <sub>b</sub> - max.	0.6 mm
d <sub>n</sub>	138.2 mm
Basic dynamic load rating - C	25.5 kN
Basic static load rating - C <sub>0</sub>	28.5 kN
Fatigue load limit - P <sub>u</sub>	1 kN
Limiting speed for grease	11000 r/min



## BEARING-MALAYSIA SDN.BHD.

Lubrication	
Limiting speed for oil lubrication	17000 mm/min
Ball - $D_w$	8.731 mm
Ball - $z$	41
$G_{ref}$	14.01 cm <sup>3</sup>
Calculation factor - $e$	0.68
Calculation factor - $Y_2$	0.87
Calculation factor - $Y_0$	0.38
Calculation factor - $X_2$	0.41
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Preload class A - $G_A$	155 N
Preload class B - $G_B$	310 N
Preload class C - $G_C$	930 N
Calculation factor - $f$	1.13
Calculation factor - $f_1$	0.99
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2C}$	1.08
Calculation factor - $f_{HC}$	1.01
Preload class A	210 N/micron
Preload class B	271 N/micron
Preload class C	411 N/micron
$d_1$	136.92 mm
$d_2$	135 mm
$D_2$	151.9 mm
$r_{1,2}$ min.	1.1 mm



## BEARING-MALAYSIA SDN.BHD.

$r_{3,4}$ min.	0.6 mm
$d_a$ min.	126 mm
$d_b$ min.	126 mm
$D_a$ max.	159 mm
$D_b$ max.	161.8 mm
$r_a$ max.	1 mm
$r_b$ max.	0.6 mm
$d_n$	138.2 mm
Basic dynamic load rating C	33.8 kN
Basic static load rating $C_0$	45 kN
Fatigue load limit $P_u$	1.02 kN
Attainable speed for grease lubrication	11000 r/min
Attainable speed for oil-air lubrication	17000 r/min
Ball diameter $D_w$	8.731 mm
Number of balls z	41
Reference grease quantity $G_{ref}$	14.01 cm <sup>3</sup>
Preload class A $G_A$	155 N
Static axial stiffness, preload class A	210 N/ $\mu$ m
Preload class B $G_B$	310 N
Static axial stiffness, preload class B	271 N/ $\mu$ m
Preload class C $G_C$	930 N
Static axial stiffness, preload class C	411 N/ $\mu$ m
Calculation factor f	1.13
Calculation factor $f_1$	0.99
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2C}$	1.08
Calculation factor $f_{HC}$	1.01



## BEARING-MALAYSIA SDN.BHD.

Calculation factor e	0.68
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67
Mass bearing	1.2 kg